

GENIEMAT[®] RST12

SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATION

PRODUCT NAME:	GenieMat RST12
DIMENSION:	Rollgood: 4' wide, 15' long (1.2 m wide, 4.6 m long)
THICKNESS:	¹⁵ / ₃₂ " (nom. 12 mm)
DENSITY:	Shall be > 1000 kg/m ³
ROLLS/PALLET:	12

TECHNICAL DATA

NATURAL FREQUENCY	Shall not be greater than 61 Hz @ 400 psf loading
HIIC (ASTM WK59631)	Shall be ≥ 57 when tested on an 8" concrete slab with tile
POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES: (ANSI 118.12)	Exceeds pass criteria
ROBINSON WHEEL TILE TEST: (ASTM C627)	Light commercial with tile
VOC EMISSIONS: (ASTM 5116)	Meets requirements for the California Department of Public Health Criteria
TEMPERATURE STABILITY:	-40°F to +240°F (-40°C to +115°C)

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2018.

[®] Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com