

GENIEMAT[®] RST15

SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat RST15

DESCRIPTION: Robust reduced sound transmission mat made from 94% recycled rubber content used when superior sound control is required in multifamily housing, high-rises, or commercial buildings.

APPLICATION: Flat, resilient underlayment that is used directly under a variety of floor finishes in wood, steel, and concrete construction, yielding exceptional results for impact sound insulation.

FEATURES AND BENEFITS:

- Significantly reduces impact sound
- Mold, bacteria, fungi, and water resistant
- Qualifies for LEED[®] points
- Can be installed directly under hard surface or resilient floor coverings
- FloorScore[®] certified

DIMENSION: Rollgood: 4' wide, 15' long (1.2 m wide, 4.6 m long)

THICKNESS: 19/32" (nom. 15 mm)

ROLL WEIGHT: 190 lb/roll (86.2 kg/roll)

ROLL AREA: 60 ft² (5.6 m²)

ROLLS/PALLET: 11

LEAD TIME: 2-3 weeks after receipt of order

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2017.

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com

GENIEMAT[®] RST15

SOUND CONTROL UNDERLAYMENT



TECHNICAL DATA

REDUCTION OF IMPACT
SOUND PRESSURE LEVEL:
(ASTM E492/E2179)

- **GenieMat RST15** tested over 8" concrete slab with vinyl plank floor covering, no ceiling, IIC 56.
- **GenieMat RST15** tested over 8" concrete slab with 3/8" laminate wood floor covering, no ceiling, IIC 56.
- The floor-ceiling assembly must be tested in an accredited laboratory within the last 5 years.

SHEET WEIGHT: 3.2 lb/ft² (15.5 kg/m²)

VOC EMISSIONS:
(ASTM 5116) Meets requirements for the California Department of Public Health Criteria

TEMPERATURE STABILITY: -40°F to +240°F (-40°C to +115°C)

CONTACT US

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2017.

The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com