

GENIEMAT[®] DH760

SOUND CONTROL UNDERLAYMENT



It's not magic, it's engineering.®

PRODUCT SPECIFICATION

Product Name:	GenieMat[®] DH760
Description:	Robust reduced sound transmission mat made from 94% recycled rubber content used when superior high frequency impact insulation is required in multifamily housing, high-rises, or commercial buildings.
Application:	Flat, resilient underlayment that is used directly under a variety of floor finishes in wood, steel, and concrete construction, yielding exceptional results for impact sound insulation.
Features and Benefits:	<ul style="list-style-type: none">• Significant reduces impact sound• Mold, bacteria, fungi, and water resistant• Qualifies for LEED[®] points• Can be installed directly under hard surface or resilient floor coverings• Achieve HIIC 60 in double glue down hardwood installation
Dimension:	Rollgood: 4' wide, 30' long (1.22 m wide, 9.14 m long)
Thickness:	1/4" (nom. 7 mm)
Density:	Shall be ~44 lb/ft ³ (~700 kg/m ³)
Roll Weight:	132 lb/roll (59.87 kg/roll)
Roll Area:	120 ft ² (11.15 m ²)
Rolls/Pallet:	15

CONTACT US | For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com | www.pliteq.com
© Pliteq Inc. 2021.

®/™Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested applications may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.

www.pliteq.com

GENIEMAT[®] DH760

SOUND CONTROL UNDERLAYMENT



It's not magic, it's engineering.®

TECHNICAL DATA

SHEET WEIGHT:	1.1 lb/ft ² (5.37 kg/m ²)
Impact Insulation Class Rating (ASTM E492):	GenieMat DH760 tested over 8" concrete slab with 3/16" vinyl plank in a floating installation, no ceiling, IIC 59 GenieMat DH760 tested over 8" concrete slab with 1/4" engineered hardwood in a floating installation, no ceiling, IIC 57 GenieMat DH760 tested over 8" concrete slab with 9/16" oak hardwood in a double glue down installation, no ceiling, IIC 54
Natural Frequency*	68 Hz @ 200 psf
HIIC (ASTM E3222)	Shall be ≥ 60 when tested over 8" concrete slab with Vinyl Plank floor Shall be ≥ 60 when tested over 8" concrete slab with hardwood flooring in a double glue down installation.
Robinson Wheel Tile Test (ASTM C627)	Light Commercial with tile
Point Load Test for Crack Isolation Membranes (ANSI 118.12)	Exceeds pass criteria
VOC Emissions (ASTM 5116)	Meets requirements for the California Department of Public Health Criteria
Temperature Stability	-40°F to +240°F (-40°C to +115°C)

* Natural Frequency is dependent on AC and DC loads.

CONTACT US | For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com | www.pliteq.com
© Pliteq Inc. 2021.

®/™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested applications may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.

www.pliteq.com