

### PRODUCT SPECIFICATION

**PRODUCT NAME:** GenieMat FAS

**DESCRIPTION:**

**GenieMat FAS** is a single component 100% solids, cross-linking, polymer-based adhesive formulated for interior installation of all thicknesses of solid/engineered wood, pre-finished and unfinished wood, bamboo and dry-back wood parquet flooring. **GenieMat FAS** also has superior concrete moisture inhibition capability (becoming waterproof when fully cured) and provides isolation for cracks up to 1/8" wide.

**GenieMat FAS** is solvent and isocyanate free, has negligible (0.5 g/L) VOC content, contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200 and is a nonflammable, low odor adhesive that meets all federal, state and local government indoor air quality regulations.

This specially formulated adhesive has good early strength buildup for immediate grab and gradually builds into a tenacious but resilient bond as the chemicals in the adhesive cross-link.

**APPLICATION:**

**GenieMat FAS** is used for bonding **GenieMat** sound control underlayments to various subfloors/substrates, and for bonding specified wood finish floors to **GenieMat** sound control underlayments.

**INSTALLATION METHOD:**

Immediate wet set installation. 60 minute working time. Use a 100 lb roller and allow 16 hours before light traffic, 24 hours before heavy traffic and 72 hours before sanding.

**BASE:**

Polymer-Resin Blend

**APPEARANCE:**

Off white, smooth, easy-to-spread mastic

**WORKING TIME:**

Approximately 60 minutes, depending on temperature and humidity

**SHELF LIFE:**

1 year in unopened container at 70°F (21°C)

**TROWEL SELECTION AND COVERAGE:**

**Installation:**

All solid wood, engineered wood & bamboo, pre-finished or unfinished, all thicknesses:

Moisture inhibitor & wood installation one-step application:

Dry-back parquet:

**GenieMat** to approved substrate:

**Trowel Size\* & Notch:**

3/16" x 1/4" x 1/2" Flat V

3/16" x 1/4" x 1/2" Flat V with Spacers

1/8" x 1/8" x 1/8" Sq.

1/16" x 1/16" x 1/16" Sq.

**Coverage:**

60-70 ft<sup>2</sup>/gal

30-35 ft<sup>2</sup>/gal

60-70 ft<sup>2</sup>/gal

Up to 120 ft<sup>2</sup>/gal

\*Trowel dimension is width x depth x spacing. Coverage is approximate and may vary depending on porosity of substrate and angle at which the trowel is held. It is the installer's responsibility to apply the proper amount of adhesive for the job condition.

For Your Project Specific Questions  
**T.** 416.449.0049 | **E.** info@pliteq.com

© Pliteq Inc. 2020.

<sup>®</sup> Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



# GENIEMAT<sup>®</sup> FAS

## FLOORING ADHESIVE SYSTEM



### PRODUCT SPECIFICATION CONTINUED

QUANTITY:	Tub: 4 gal (15.1 L)
DENSITY:	Max. 10.2 lb/gal (1.2 kg/L)
LEAD TIME:	2-3 weeks after receipt of order

### TECHNICAL DATA

PERCENT VOLATILE:	0%
VOC CONTENT:	<0.50 grams/L
APPLICATION TEMPERATURE:	60 - 85°F (15 - 30°C)
APPLICATION RELATIVE HUMIDITY:	30% - 65%
FREEZE/THAW STABILITY:	Stable to 10°F (-12°C)
RELATIVE HUMIDITY TEST (ASTM F2170):	Maximum 75% Maximum 90% when used as moisture inhibited system, as per above*
CALCIUM CHLORIDE TEST (ASTM F1869):	Maximum 3 lb/1000 ft <sup>2</sup> /24 hrs Maximum 10 lb/1000 ft <sup>2</sup> /24 hrs when used as moisture inhibited system, as per above*

\*When trowel with spacers used per moisture inhibitor system above.

## CONTACT US

For Your Project Specific Questions  
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2020.

<sup>®</sup> Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



[www.pliteq.com](http://www.pliteq.com)