

# GENIEMat® FAS

MODIFIED SILANE FLOORING ADHESIVE  
FOR MOISTURE BARRIER APPLICATIONS



## PRODUCT SPECIFICATION

PRODUCT NAME: **GenieMat FAS**

**DESCRIPTION:** **GenieMat FAS** is a Modified Silane, one component 100% solids, solvent free and isocyanate free adhesive that has <0.1 g/L VOC content, contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200 and is a nonflammable, low odor adhesive that meets all federal, state, and local governmental indoor air quality regulations. This specially formulated adhesive has good early strength buildup for immediate grab and quickly builds into a tenacious but elastic resilient bond as the adhesive cross-links.

This adhesive is easy to clean up, even after it has dried on the flooring surface. When used according to directions this adhesive forms a solid membrane below the flooring to protect it from subfloor moisture. Concrete floors over one year old with high moisture readings are usually indicative of a chronic underlying moisture source problems which must be determined prior to the flooring installation.

**APPLICATION:** **GenieMat FAS** is ideal for glue-down installations on all grades, for **GenieMat** sound control underlayments, a broad variety of rubber/recycled rubber/linoleum floors, all types of engineered, solid or acrylic impregnated wood flooring and bamboo, designed to be installed using a wet-set glue down installation method.

**INSTALLATION METHOD:** Immediate wet set installation. Use a 100 lb 3-section roller and allow 6 hours before light traffic, heavy traffic and furniture.

## TECHNICAL DATA

BASE: MS Polymer

APPEARANCE: Off-white

APPLICATION TEMPERATURE: 60 - 95°F (15 - 35°C)

APPLICATION RELATIVE HUMIDITY: 30% - 65%

RELATIVE HUMIDITY TEST (ASTM F2170): 95% - Adhesive tolerance and for moisture barrier applications with specified notched trowel. Otherwise follow flooring manufacturers specifications.

SUBSTRATE MVER (ASTM F1869): 15 lbs - Adhesive tolerance and for moisture barrier applications with specified notched trowel. Otherwise follow flooring manufacturers specifications.

SUBSTRATE pH (ASTM F710): No testing required (5-14) - For moisture barrier applications with specified notched trowel. Otherwise follow flooring manufacturers specifications.

SUBSTRATE Porosity (ASTM F3191): Must Pass (CSP 1+) - For moisture barrier applications with specified notched trowel. Otherwise follow flooring manufacturers specifications.

# GENIEMAT<sup>®</sup> FAS

## MODIFIED SILANE FLOORING ADHESIVE FOR MOISTURE BARRIER APPLICATIONS



<b>MOISTURE BARRIER:</b>	Protects flooring against substrate moisture vapor up to (95% RH and 15lbs MVER) with specified moisture barrier notched trowel & is not impacted by topical liquids
<b>FLASH TIME:</b>	N/A
<b>WORKING TIME:</b>	45 minutes
<b>CURE TIME:</b>	12 hours
<b>LIGHT TRAFFIC:</b>	6 hours
<b>HEAVY TRAFFIC:</b>	6 hours
<b>ROLLING LOADS:</b>	N/A
<b>CLEANING:</b>	While wet: Use a damp cloth and water to remove. While soft: Use denatured alcohol, mineral spirits, or an adhesive remover/stripper. Always check compatibility on a piece of scrap flooring.
<b>STORAGE:</b>	50-90°F (10-32°C)
<b>SHELF LIFE:</b>	1 year [Unopened Container at 70°F]
<b>FREEZE/THAW STABILITY:</b>	Protect from Freezing; Stable to 10°F (-12°C) [3 cycles]
<b>VOC CONTENT:</b>	<0.1g/L
<b>CERTIFICATION:</b>	Floor Score <sup>®</sup> ; Green Label Plus <sup>®</sup> ; GREENGUARD <sup>®</sup> - Gold; Material Health Certificate - Silver; mindful MATERIAL Library; Red List Free (LBC version 3.1); USGBC Member; LEED v4/4.1 Points
<b>QUANTITY:</b>	Pail: 4 gal (15.1 L)

# GENIEMAT® FAS








MODIFIED SILANE FLOORING ADHESIVE  
FOR MOISTURE BARRIER APPLICATIONS



## TROWEL SELECTION AND COVERAGE:

Always refer to the flooring manufacturers recommendations for substrate condition requirements. Moisture barrier application methods can be used to protect the flooring from elevated slab conditions for RH/MVER/CaCl<sub>2</sub>/pH up to the stated adhesive specifications with the specified moisture barrier notched trowel.

### TROWEL SELECTION AND COVERAGE:

Flooring Types:	Tool* (Images not to scale):	Estimated Coverage:
<b>BOND ONLY</b>		
<b>GenieMat to Porous Substrate</b>	$\frac{1}{16}'' \times \frac{1}{16}'' \times \frac{1}{16}''$ (1.6mm x 1.6mm x 1.6mm) Sq. Notch	 75-125 ft <sup>2</sup> /gal (1.84-3.07 m <sup>2</sup> /l)
<b>GenieMat to Non-Porous Substrate</b> Sheet/rolls to <b>GenieMat</b> Tiles/Planks to <b>GenieMat</b>	$\frac{1}{16}'' \times \frac{1}{32}'' \times \frac{1}{32}''$ (1.6mm x 0.8mm x 0.8mm) U Notch	 180-250 ft <sup>2</sup> /gal (4.42-6.14 m <sup>2</sup> /l)
<b>Turf to GenieMat</b>	$\frac{1}{8}'' \times \frac{1}{8}'' \times \frac{1}{16}''$ (3.2mm x 3.2mm x 1.6mm) U Notch	 50-65 ft <sup>2</sup> /gal (1.23-1.60 m <sup>2</sup> /l)
<b>Parquet Hardwood</b>	$\frac{1}{8}'' \times \frac{1}{8}'' \times \frac{1}{16}''$ (3.2mm x 3.2mm x 1.6mm) Sq. Notch	 60-70 ft <sup>2</sup> /gal (1.47-1.72 m <sup>2</sup> /l)
All solid wood, engineered wood & bamboo, pre-finished or unfinished, all thicknesses	$\frac{3}{16}'' \times \frac{1}{4}'' \times \frac{5}{16}''$ (4.8mm x 6.4mm x 7.9mm) V Notch	 Up to 50 ft <sup>2</sup> /gal (Up to 1.23 m <sup>2</sup> /l)
<b>MOISTURE BARRIER</b>		
All solid wood, engineered wood (planks less than 6' [1.83m] long and 5" [127mm] wide) & bamboo, pre-finished or unfinished	$\frac{1}{4}'' \times \frac{1}{4}''$ (6.4mm x 6.4mm) V Notch	 25-30 ft <sup>2</sup> /gal (0.61-0.74 m <sup>2</sup> /l)
All solid wood, engineered wood (planks greater than 6' [1.83m] long and 5" [127mm] wide) & bamboo, pre-finished or unfinished	$\frac{1}{2}'' \times \frac{15}{32}''$ (12.7mm x 11.9mm) V Notch	 Up to 20 ft <sup>2</sup> /gal (Up to 0.49 m <sup>2</sup> /l)



# AROUND THE WORLD.

## CONTACT US

### PLITEQ NORTH AMERICA

131 Royal Group Crescent  
Vaughan, ON  
L4H 1X9 Canada

T. + 1 416 449 0049

[info@pliteq.com](mailto:info@pliteq.com)  
[www.pliteq.com](http://www.pliteq.com)

### PLITEQ UK

Office 205  
Orega High Holborn,  
16 High Holborn,  
London,  
WC1V 6BX

T. + 44 2039846444

[info@pliteq.co.uk](mailto:info@pliteq.co.uk)  
[www.pliteq.co.uk](http://www.pliteq.co.uk)

### PLITEQ MIDDLE EAST

European Business Centre  
Dubai Investment Park  
PO Box 473 512  
Dubai, UAE

T: +971 4 567 4944

[info@pliteq.ae](mailto:info@pliteq.ae)  
[www.pliteq.ae](http://www.pliteq.ae)

### PLITEQ ASIA PACIFIC

101 Cecil Street #19-13  
Tong Eng Building Singapore  
069533

T. +65 6813 2017

[info@pliteq.sg](mailto:info@pliteq.sg)  
[www.pliteq.sg](http://www.pliteq.sg)

### PLITEQ AUSTRALIA & NEW ZEALAND

72 York Street, South  
Melbourne, VIC, 3205

T. + 61 3 9018 7696  
T.+ 61 476 757 736

[info@pliteq.com.au](mailto:info@pliteq.com.au)  
[www.pliteq.com.au](http://www.pliteq.com.au)

