

PRODUCT SPECIFICATION

PRODUCT NAME: GenieMat FASHM

DESCRIPTION: GenieMat FASHM is a one-component, 100% solids, cross-linking, modified silane polymer-based adhesive. It is solvent-free, water-free, and isocyanate-free, non-flammable, has low-odor, negligible VOC content, contains no hazardous chemicals as per OSHA Regulation CFR 1910.1200, and meets all federal, state, and local government indoor air quality regulations. This specially formulated adhesive features extremely low-permeability ratings, withstands maximum moisture levels of 10 lbs and 90% RH, is unaffected by concrete slab alkalinity, has good early strength buildup for immediate grab and gradually builds into a tenacious but resilient bond as the chemicals in the adhesive cross-link, and plasticizer migration resistance that allows installation of a broad variety of vinyl floor products.

APPLICATION: GenieMat FASHM is used in high-moisture applications for bonding GenieMat sound control underlayments to various subfloors/substrates, and for bonding specified finish floors and coverings to GenieMat sound control underlayments.

INSTALLATION METHOD: Immediate wet set installation. 45 minute working time. Use a 75-100 lb roller.

BASE: Modified Silane Polymer Blend

APPEARANCE: White, smooth, creamy, easy-to-trowel

WORKING TIME: Approximately 45 minutes, depending on temperature and humidity

SHELF LIFE: 1 year in unopened container at 70°F (21°C)

TROWEL SELECTION AND COVERAGE:

Installation:	Trowel Size* & Notch:	Coverage:
GenieMat to substrate	1/16" x 1/16" x 1/16" Sq.	Up to 150-200 ft ² /pail
Sheet goods to GenieMat	1/16" x 1/16" x 1/16" Sq.	Up to 150-200 ft ² /pail
Vinyl tile and plank to GenieMat	1/16" x 1/32" x 1/32" U	Up to 200 - 300 ft ² /pail

*Trowel dimension is width x depth x spacing. Coverage is approximate and may vary depending on porosity of substrate and angle at which the trowel is held. It is the installer's responsibility to apply the proper amount of adhesive for the job condition.

For Your Project Specific Questions
T. 416.449.0049 | **E.** info@pliteq.com

© Pliteq Inc. 2020.

®™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



GENIEMAT[®] FASHM

SOUND CONTROL ADHESIVE



PRODUCT SPECIFICATION CONTINUED

QUANTITY:	Tub: 2 gal (7.6 L)
DENSITY:	Max. 8.0 lb/gal (0.96 kg/L)
LEAD TIME:	2-3 weeks after receipt of order

TECHNICAL DATA

PERCENT VOLATILE:	0%
VOC CONTENT:	0.1 grams/L *VOC Content (SCAQMD Rule#1168)*
RELATIVE HUMIDITY TEST (ASTM F2170):	No relative humidity test required
CALCIUM CHLORIDE TEST (ASTM F1869):	No calcium chloride test required
APPLICATION TEMPERATURE:	65 - 95°F (18 - 35°C)
APPLICATION RELATIVE HUMIDITY:	30 - 60%
FREEZE/THAW STABILITY:	Stable to 10°F (-12.2°C)

CONTACT US

For Your Project Specific Questions
T. 416.449.0049 | E. info@pliteq.com

© Pliteq Inc. 2020.

[®] Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



www.pliteq.com