GENIEMAT® PMI05R





Product Specification	
PRODUCT NAME:	GenieMat PMIo5R
DESCRIPTION:	Flat, resilient, recycled rubber perimeter isolation strip that is used to build a tub around the floor so that no hard surface (floor covering) touches any hard vertical surface (protrusion or wall).
Application:	To be attached at the base of the perimeter wall of the entire subfloor, as well as around the perimeter of any protrusions, prior to unrolling and installing GenieMat underlayment products, in order to isolate or break the vibration transmission path between the floor and the wall.
Features and Benefits:	Reduces noise flanking in acoustic-isolated assemblies Bacteria, fungi, and water resistant Easy to unroll, cut, and install
Dimension:	Rollgood: 3" wide, 30' long (0.1 m wide, 9.1 m long)
SHEET THICKNESS:	¹ / ₅ " (nom. 5 mm)
SHEET WEIGHT:	0.74 lb/ft² (3.6 kg/m²)

CONTACT US

ROLL WEIGHT:

COVERAGE:

LEAD TIME:

For Your Project Specific Questions **T.** 416.449.0049 | **E.** info@pliteq.com



^{***} Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.

7.8 lb/roll (3.54 kg/roll)

2-3 weeks after receipt of order

30 linear ft

